

Product Data Sheet

SoSafe™ Blue Graffiti Remover – for Non-Sensitive Surfaces

Ideal to remove graffiti from: Brick, concrete, blocks, sheet metal, train exteriors, mortar, grout, marble, granite, slate, stone, stucco, unpainted shutters, terracotta, terrazzo, pebblecrete, pavers and other difficult to remove graffiti stains.

Product Description

SoSafe™ Blue graffiti remover for non-sensitive surfaces is a broad-spectrum graffiti remover ideal for use on most porous, non-sensitive or other difficult surfaces to remove spray paint, marker, poster glue, shoe polish, chewing gum and crayon.

SoSafe™ Blue graffiti remover is available in liquid or sprayable gel form. Sprayable gel when applied to a vertical surface will hold in position until the user rinses, reducing the quantity of product required to remove graffiti as well as preventing the graffiti dye running down the walls. SoSafe™ Blue Liquid is popular with contractors as it penetrates deeper into the surface and is generally used in conjunction with high-pressure equipment.

Characteristics

- * pH Neutral
- * Non-Flammable
- * Non-Hazardous
- * Biodegradable
- * Non-Toxic
- * Non-Corrosive
- * Water Neutralised

Tools / Equipment

To remove graffiti from difficult surfaces quickly it is recommended to have high pressure available, it is still possible to achieve great results without high pressure washing, though a little more time maybe required.

- * Gloves
- * Graffiti Remover
- * Scourer / Nylon Brush
- * Applicator (Sprayer / Paint Brush / Roller)
- * Water Bucket / Hose / High Pressure Washer
- * Chemical Goggles
- * White Rag

Safety

When using graffiti remover follow safety directions on the label, wear appropriate attire including - enclosed shoes, gloves and non-vented goggles.

Application Procedure

1. Dry surface - SoSafe Blue is designed to work on dry

surfaces. *NOTE: Use SoSafe Professional with Shadow Chaser and high pressure washer, if dry wall is not possible.*

2. Scrub surface with a scourer, nylon hard bristle or wire brush, to break the seal.

3. Apply graffiti removing product by sprayer, paint brush or roller *NOTE: Sprayable gel should always be sprayed. The spraying action causes the product to thicken.*

4. Wait a minimum of 3 minutes.

5a. **NO HIGH PRESSURE EQUIPMENT:** Scrub surface with a scourer, nylon hard bristle or wire brush in a circular motion. When the graffiti moves, the bond between the graffiti and the surface is breaking. To remove / neutralise product, rinse wall with water.

NOTE: Often the surface will not appear to be completely free of graffiti until the wall is washed.

5b. **HIGH PRESSURE EQUIPMENT:** High-pressure water blaster (hot water preferable), working slowly back facing the wind at a 45° angle, approx 20 cm away from the surface.

9. Coat surface with a semi sacrificial surface graffiti protection such as So Safe Safety Shield, to make it easier for future graffiti removal.

*On particularly difficult surfaces SoSafe Professional & Shadow Chaser may be required.

Product Coverage

Coverage rates for graffiti removal vary significantly depending on various factors such as: age of the graffiti, type of graffiti, thickness of the graffiti, temperature, moisture, porosity, substrate and equipment used. A typical spray paint tag 1 metre x 2 metres on a brick wall will require approximately 400mLs to 1 Litre of product.

Pack Sizes

12x750mL (Retail Only) / 10x1Lt / 3x5Lt / 25Lt

Disclaimer

To the best of our knowledge and belief, the information is true and accurate at the time of publication. Since the conditions of use are out of the agents/distributors/manufacturers control, the end user must satisfy themselves by prior testing the product is suitable for their specific application.

SoSafe Specialty Products Pty Limited ABN 73 001 553 699
Postal: PO Box 386, Brookvale NSW 2100 Australia
Phone: (+612) 9938 1800
Fax: (+612) 9905 0979
Email: sales@sosafe.com.au
Web: www.sosafe.com.au