

Product Data Sheet

Shadow Chaser

Ideal to remove old graffiti, graffiti shadows and ghosts from: Brick, concrete, blocks, sheet metal, train exteriors, mortar, grout, marble, granite, slate, stone, stucco, unpainted shutters, terracotta, terrazzo, pebblecrete, pavers and other difficult to remove graffiti stains.

Product Description

The removal of some graffiti types such as very old graffiti requires a special approach to removal. This approach is a combination of knowledge, skill and chemical technology.

Shadow Chaser forms part of this revolutionary tool in the battle against graffiti removal, increasing the speed, performance and efficiency of graffiti removal crews. Shadow Chaser should only be used by trained professional graffiti removal technicians, SoSafe™ trained graffiti removal crews or SoSafe™ approved training centres for best results.

Shadow Chaser is only available for use by professionals. Shadow Chaser is a corrosive formulation designed to work in conjunction with SoSafe™ Professional Edition (Red Label). Shadow Chaser has been specially formulated for stubborn graffiti stains that cannot be removed by conventional means and requires a professional approach.

NOTES:

- Pay attention to all safety precautions on the packaging & MSDS.
- All safety equipment is mandatory.
- Shadow Chaser must not be sprayed / atomised.
- Aluminium is affected by Shadow Chaser do not allow contact, if contact occurs wash thoroughly with water.

Characteristics

- * Non-Flammable
- * Biodegradable
- * CO₂ Neutralised
- * Corrosive

NOTE: Shadow Chaser absorbs CO₂ from the atmosphere reducing atmospheric greenhouse gases. In normal application Shadow Chaser will be pH neutral within one hour of application (harmless). In general usage once a surface is pressure washed the product is diluted to less than 0.5%.

Tools / Equipment

To remove graffiti from difficult surfaces quickly it is recommended to have high pressure available, it is still possible to achieve great results without high pressure though a little more time maybe required.

- * Gloves
- * Non-Vented Goggles
- * Applicator (Sprayer / Paint Brush / Roller)
- * High Pressure Washer
- * Graffiti Remover

Safety

When using graffiti remover follow safety directions on the label, wear appropriate attire including - enclosed shoes, gloves and non-vented goggles.

Application Procedure

1. Dry surface is preferable, however product will work on damp surface.
2. Apply SoSafe™ Professional by sprayer, paint brush or roller and wait a minimum of 3 minutes.
3. Apply Shadow Chaser directly over the top of the graffiti remover:

SMALL AREAS – Use paint brush using a small container Shadow Chaser, keep your wrist down while applying, so not to have product run down your glove, do not spray.

LARGE AREAS – Use paint roller and tray, apply slowly (take care not to come into direct contact with Shadow Chaser), do not spray (follow label application and safety directions) **NOTE: Apply Shadow Chaser with care, follow all safety procedures. DO NOT SPLASH.**

4. Leave Shadow Chaser for a minimum of 4 minutes.

5. Remove chemicals with a high-pressure water blaster (hot water preferable), working slowly back facing the wind at a 45° angle at 3000psi for hard surfaces or < 900 psi on erodible surfaces.

Product Coverage

Coverage rates for graffiti removal vary significantly depending on various factors such as: age of the graffiti, type of graffiti, thickness of the graffiti, temperature, moisture, porosity, substrate and equipment used. A typical spray paint tag 1 metre x 2 metres on a brick wall will require approximately 150mLs to 800mLs of product.

Pack Sizes

3x5Lt / 24Lt

Disclaimer

To the best of our knowledge and belief, the information is true and accurate at the time of publication. Since the conditions of use are out of the agents/distributors/manufacturers control, the end user must satisfy themselves by prior testing the product is suitable for their specific application.

SoSafe Specialty Products Pty Limited ABN 73 001 553 699
Postal: PO Box 386, Brookvale NSW 2100 Australia
Phone: (+612) 9938 1800
Fax: (+612) 9905 0979
Email: sales@sosafe.com.au
Web: www.sosafe.com.au